

### Specifications

- IP protection rating 65
- OIML & EU approval class II
- Measuring system : Tuning-fork vibration method
- Power supply : Dedicated AC adapter (100-240 VAC, 12 VDC)
- Output : RS232C (D-sub 9 P)
- Display : Dual LCD display with backlit
- Scale cable length : 1m (extended to 5m or 10m as factory option)
- Weight : External weight type 18kg, Internal weight type 19kg

### External weight types

Model name	HJ17K0.1S	HJ22K0.1S	HJ33K0.1S	HJ62K0.1DS	
Capacity	17kg	22kg	33kg	6200g	62kg
Readability (d)	0.1g	0.1g	0.1g	0.1g	1g
Verification intervals (e)	1g	1g	1g	1g	
Non-linearity	±0.3g	±0.3g	±0.3g	±0.3g	±3g
Repeatability (σ)	0.1g	0.1g	0.1g	0.1g	1g
Pan size	400 x 350 mm				
Dimension (LDH)	350 x 482 x 175mm (350 x 482 x 700mm when pole option installed)				
Calibration	With external weight				

### Internal weight types

Model name	HJ17K0.1SR	HJ22K0.1SR	HJ33K0.1SR	HJ62K0.1DSR	
Capacity	17kg	22kg	33kg	6200g	62kg
Readability (d)	0.1g	0.1g	0.1g	0.1g	1g
Verification intervals (e)	1g	1g	1g	1g	
Non-linearity	±0.3g	±0.3g	±0.3g	±0.3g	±3g
Repeatability (σ)	0.1g	0.1g	0.1g	0.1g	1g
Pan size	400 x 350 mm				
Dimension (LDH)	350 x 482 x 175mm (350 x 482 x 700mm when pole option installed)				
Calibration	With internal and external weight				

### Option

<b>HJK-DU</b>	Hook for hanging weighing
<b>HJK-LM</b>	Relay output *1,
<b>HJK-R4</b>	RS422 output *1 *2,
<b>HJK-BT</b>	Internal rechargeable battery *1,
<b>HJK-PK</b>	Pole kit for Separate type
<b>HJK-PU</b>	Extended scale cable 5 m / 10 m (factory option),


\*1 Relay output, RS422 output and Internal rechargeable battery cannot be installed together.  
 \*2 When RS422 output is installed, the standard RS232C output is not available.

### Peripherals

<b>Printer</b>	CBM-910II
<b>Free software</b>	RTS tool (freely available in official website)



With optional pole kit



Indicator mounting bracket (provided as standard)

Distributed by:



The contents of this catalogue are subject to change due to modifications and/or other reasons.

3B.2102

## Precision platform scale

# HJKseries

More efficient precision weighing in manufacturing process

Water-proof, washable by water

High durability

Water & dust proof IP rating 65

High precision



SHINKO DENSHI CO., LTD.

## SHINKO DENSHI CO., LTD.

Head office

Tokyo:3-9-11 YUSHIMA, BUNKYO-KU, TOKYO 113-0034

Phone: +81-3-3831-9656 Fax: +81-3-5818-6066

[Development /Manufacturing] Tsukuba Plant

URL : <https://www.vibra.co.jp/global/>

E-mail : [shinko-denshi@vibra.co.jp](mailto:shinko-denshi@vibra.co.jp)

## Water-proof structure Easy to clean

Because both of platform and indicator are made from stainless steel they are highly resistant to physical shocks and chemical materials.  
Easy to clean by water after operation.



## High degree of usability For more efficient weighing operation

User-friendly key configurations, reasonable menu-tree and short stabilization time make possible efficient and comfortable weighing operation.



## Dust-proof structure Highly resistant to severely dusty environment

IP65 dust-proof structure ensures reliable weighing results even in severely dusty environment.  
It also prevents contamination problems.



## High durability in precision weighing enabled by Tuning-fork sensor

Innovative and heavy-duty tuning-fork sensor provides everlasting excellent performance in precision weighing in various manufacturing processes.

